



LUZHONG 120-130HP TRACTOR MAIN SPECIFICATION

Model		LZ1200	LZ1250	LZ1300	LZ1204	LZ1254	LZ1304	
Type		2WD Wheeled Type			4WD Wheeled Type			
Dimensions of Tractor(mm)	Length (to front ballast)	2WD:4260 4WD:4630						
	Width	2050						
	Height (to the exhaust vent)	2510						
	Wheelbase	2200						
	Tread	Front Wheel	2WD: 1385~1685 (Usual 1485) 4WD:1610					
		Rear Wheel	1620~2020(Usual 1620)					
Min.Ground Clearance		430			405			
Structure weight (kg)		3250			3540			
Ballast weight (kg)	Front ballast	250						
	Rear ballast	170 , 340 , 510 (optional)						
Engine	Model	LR6B5-23						
	Type	Vertical,6-Cylinder,Water Cooled and 4-stroke						
	Rated Power(kw)	88.2	91.9	95.6	88.2	91.9	95.6	
	Rated speed (r/min)	2300						
	Fuel	Diesel						
Tyre	Front Wheel	6.5-20			12.4-24			
	Rear Wheel	14.9-30/16.9-34			16.9-34/18.4-30			
Clutch		Dual-stage clutch						
Steering		Power steering						
Transmission Type		16F+8R						
Suspension Type		Three-point linkage Category II						
Lifting capacity(at point of 610mm) KN		22(Common lifter)/32.25(Higher pressure lifter)						
Lifting capacity(origin)KN		37(Common lifter)/54.6(Higher pressure lifter)						
PTO	Type and Rev	Semi-independent Type 540/1000						
	Spline Size	F35 Rectangle Spline with 6 teeth						

Structure and specification are subject to change without notice.

120-130HP TRACTOR

Models:

Luzhong-1200 tractor, 120HP 2WD, with 6-cylinder diesel engine

Luzhong-1250 tractor, 125HP 2WD, with 6-cylinder diesel engine

Luzhong-1300 tractor, 130HP 2WD, with 6-cylinder diesel engine

Luzhong-1204 tractor, 120HP 4WD, with 6-cylinder diesel engine

Luzhong-1254 tractor, 125HP 4WD, with 6-cylinder diesel engine

Luzhong-1304 tractor, 130HP 4WD, with 6-cylinder diesel engine

