



## LUZHONG 140-160HP TRACTOR MAIN SPECIFICATION

Model		LZ1404	LZ1504	LZ1604	
Type		4x4			
Dimensions of Tractor(mm)	Length (to front ballast)	5360			
	Width	2560			
	Height (to the exhaust vent)	3120			
	Wheelbase	2582			
	Tread	Front Wheel	1784-2202( Usual 1940)		
		Rear Wheel	1650-2285(Usual 1750)(18.4-34)/1620-2420(Usual 1850)(18.4-38)		
Min.Ground Clearance		430			
Structure weight (kg)		4900			
Ballast weight (kg)	Front ballast	250			
	Rear ballast	170 , 340 , 510 (optional)			
Engine	Model	LR6M3Z-23			
	Type	Vertical,6-Cylinder,Water Cooled and 4-stroke			
	Rated Power(kw)	103	110.3	117.9	
	Rated speed (r/min)	2300			
	Fuel	Diesel			
Tyre	Front Wheel	14.9-26			
	Rear Wheel	18.4-38			
Clutch		Dual-stage clutch			
Steering		Power steering			
Transmission Type		16F+8R			
Suspension Type		Three-point linkage Category II			
Lifting capacity(at point of 610mm) KN		≥35			
Lifting capacity(origin)KN		≥51.94			
PTO	Type and Rev	Semi-independent Type 540/1000			
	Spline Size	F35 Rectangle Spline with 6 teeth			

Structure and specification are subject to change without notice.

## 140-160HP TRACTOR

Models:

Luzhong-1404 tractor, 140HP 4WD, with 6-cylinder diesel engine

Luzhong-1504 tractor, 150HP 4WD, with 6-cylinder diesel engine

Luzhong-1604 tractor, 160HP 4WD, with 6-cylinder diesel engine

