

40-50HP (TE) TRACTOR





LUZHONG TE40-50HP TRACTOR MAIN SPECIFICATION

Model		LZ400B-TE	LZ404B-TE	LZ450B-TE	LZ454B-TE	LZ500B-TE	LZ504B-TE	
Type		4 x 2	4 x 4	4 x 2	4 x 4	4 x 2	4 x 4	
Dimensions of Tractor(mm)	Length (to front ballast)	3030						
	Width	1470						
	Height (to the exhaust vent)	1900						
	Tread	Front Wheel	1300 Fixed or 1100~1300 Adjusted					
		Rear Wheel	1300 Fixed or 1300~1350 Adjusted					
	Axle Base		1710					
Min.Ground Clearance		347.5						
Structure weight (kg)		1500						
Ballast weight (kg)	Front ballast	56						
	Rear ballast	112						
Engine	Model	490	490	490	490	4100	4100	
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke						
	Rated Power(kw)	29.4	29.4	33.1	33.1	36.8	36.8	
	Rated speed (r/min)	2400						
	Fuel	Diesel						
Tyre	Front Wheel	6.50-16						
	Rear Wheel	11.2-24						
Clutch		Dual-stage clutch						
Steering		power steering						
Transmission Type		8+2 or 8+8 with shuttle gearshift or (8+2)×2 with creeper shift						
Suspension Type		3-point links						
PTO	Type and Rev	Semi-independent Type 540/1000						
	Spline Size	F35 Rectangle Spline with 6 teeth						

Structure and specification are subject to change without notice.