



LUZHONG 35-45HP GARDEN TRACTOR MAIN SPECIFICATION

Model		LZ350G	LZ400G	LZ450G	LZ354G	LZ404G	LZ454G	
Type		4 x 2	4 x 2	4 x 2	4 x 4	4 x 4	4 x 4	
Dimensions of Tractor(mm)	Length	2760						
	Width	1120 to 1475						
	Height	1140						
	Tread	Front Wheel	880/960/1080/1130 adjustable					
		Rear Wheel	880-1600 adjustable					
	Axle Base		1650					
Min.Ground Clearance		260						
Structure weight (kg)		1100						
Ballast weight (kg)	Front ballast	56						
	Rear ballast	110						
Rated traction force (N)		5200	5940	6680	6900	7880	8870	
Engine	Model	4L22	4L23	JD490	4L22	4L23	JD490	
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke						
	Rated Power(kw)	25.7	29.4	33.1	25.7	29.4	33.1	
	Rated speed (r/min)	2400						
	Fuel	Diesel						
Tyre	Front Wheel	450-12、450-14(2WD); 600-12(4WD)						
	Rear Wheel	7.5-20、9.5-16、13.6-16						
Clutch		Single-stage clutch						
Steering		power steering						
Transmission Type		8+2 or (8+2)x2 with creeper shift						
Suspension Type		3-point links						
PTO	Type and Rev	Semi-independent Type 540						
	Spline Size	F35 Rectangle Spline with 6 teeth						

Structure and specification are subject to change without notice.

35-45HP GARDEN TRACTOR

