

TB 40-55HP TRACTOR





LUZHONG 40-55HP 4WD TRACTOR MAIN SPECIFICATION

Model		LZ404-TB	LZ454-TB	LZ504-TB	LZ554-TB	
Type		4WD Wheeled Type				
Dimensions of Tractor(mm)	Length (to front ballast)	3835				
	Width	1620				
	Height (to the exhaust vent)	2220				
	Tread	Front Wheel	1300 Fixed or 1200~1500 Adjusted			
		Rear Wheel	1300 Fixed or 1200~1500 Adjusted			
	Axle Base		2030			
Min.Ground Clearance		325				
Structure weight (kg)		1665		1734	1790	
Ballast weight (kg)	Front ballast	140				
	Rear ballast	200				
Rated traction force (N)		11000	11300	11600	11600	
Engine	Model	490	495	4100	4105	
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke				
	Rated Power(kw)	29.4	33	36.7	40.4	
	Rated speed (r/min)	2400				
	Fuel	Diesel				
Tyre	Front Wheel	8.3-20				
	Rear Wheel	12.4-28				
Clutch		Dual-stage clutch				
Steering		power steering				
Transmission Type		8+4 or 8+8 with shuttle gearshift or 16+4 with creeper shift				
Suspension Type		3-point links				
PTO	Type and Rev	Semi-independent Type 540/1000				
	Spline Size	F35 Rectangle Spline with 6 teeth				

Structure and specification are subject to change without notice.