



LUZHONG 55-65HP GARDEN TRACTOR MAIN SPECIFICATION

Model		LZ550G	LZ554G	LZ600G	LZ604G	LZ650G	LZ654G	
Type		4x2	4x4	4x2	4x4	4x2	4x4	
Dimensions of Tractor(mm)	Length(With front ballast)	3450						
	Width	1120 to 1475						
	Height	1250						
	Tread	Front Wheel	880/960/1080/1130 adjustable					
		Rear Wheel	880-1600 adjustable					
	Axle Base		1830					
Min.Ground Clearance		240						
(kg) Structure weight		1550						
Ballast weight (kg)	Front ballast	110						
	Rear ballast	100						
Rated traction force (N)		9500	11800	10300	12800	11200	13900	
Engine	Model	4105	4105	4105	4105	4105	4105	
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke						
	Rated Power(kw)	40.4	40.4	44.1	44.1	47.8	47.8	
	Rated speed (r/min)	2400						
	Fuel	Diesel						
Tyre	Front Wheel	450-12 (2WD); 600-12 (4WD)						
	Rear Wheel	11.2-20						
Clutch		Dual-stage clutch						
Steering		power steering						
Transmission Type		8+4 or 16+4 with creeper shift						
Suspension Type		3-point links						
Suspension Type	Type and Rev	Semi-independent Type 540/1000						
PTO	Spline Size	F35 Rectangle Spline with 6 teeth						

Structure and specification are subject to change without notice.

1. Designed for small farm, orchards, greenhouses and gardens specially, it has low height, narrow track. Rear 4 hweels is optional.
2. Directly connected with 4 cylinder engine, 55/60/65 HP.
3. Basic type 8F+4R, and 8F+8R shuttle gears, 16F+8F creeper gears is optional.
4. Standard Cat.II 3-point linkage, most farm implements available.



**A NEW TRACTOR
FOR THE VEGETABLE GREENHOUSES AND ORCHARDS**

