



LUZHONG 90-110HP TRACTOR MAIN SPECIFICATION

Model			LZ900	LZ950	LZ1000	LZ1100	LZ904	LZ954	LZ1004	LZ1104
Туре			2WD Wheeled Type 4WD Wheeled Type							
Dimensions of Tractor(mm)	Length (to front ballast)		2WD:4160 4WD:4530							
	Width		2050							
	Height (to the exhaust vent)		2510							
	Wheelbase		2200							
	Tread	Front Wheel	2WD: 1385~1685 (Usual 1485) 4WD:1610							
		Rear Wheel	1620~2020(Usual 1620)							
	Min.Ground Clearance		430				405			
Structure weight (kg)			3010 3300							
Ballast weight	Front ballast		250							
(kg)	Rear ballast		170 , 340 , 510 (optional)							
Engine	Model		LR4M3Z-23							
	Туре		Vertical,4-Cylinder,Water Cooled and 4-stroke							
	Rated Power(kw)		66.1	69.9	73.5	81	66.1	69.9	73.5	81
	Rated speed (r/min)		2300							
	Fuel		Diesel							
Tyre	Front Wheel		6.5-20				12.4-24			
	Rear Wheel		14.9-30 (16.9-34)				16.9-34			
Clutch			Dual-stage clutch							
Steering			Power steering							
Transmission Type			16F+8R							
Suspension Type			Three-point linkage Category II							
Lifting capacity(at point of 610mm) KN			22(Common lifter)/32.25(Higher pressure lifter)							
Lifting capacity(origin)KN			37(Common lifter)/54.6(Higher pressure lifter)							
PTO	Type and Rev		Semi-independent Type 540/1000							
	Spline Size		F35 Rectangle Spline with 6 teeth							

Structure and specification are subject to change without notice.

90-100HP TRACTOR

