



**LUZHONG 90-110HP TRACTOR MAIN SPECIFICATION**

Model		LZ900	LZ950	LZ1000	LZ1100	LZ904	LZ954	LZ1004	LZ1104	
Type		2WD Wheeled Type				4WD Wheeled Type				
Dimensions of Tractor(mm)	Length (to front ballast)	2WD:4160 4WD:4530								
	Width	2050								
	Height (to the exhaust vent)	2510								
	Wheelbase	2200								
	Tread	Front Wheel	2WD: 1385~1685 (Usual 1485) 4WD:1610							
		Rear Wheel	1620~2020(Usual 1620)							
Min.Ground Clearance		430				405				
Structure weight (kg)		3010				3300				
Ballast weight (kg)	Front ballast	250								
	Rear ballast	170 , 340 , 510 (optional)								
Engine	Model	LR4M3Z-23								
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke								
	Rated Power(kw)	66.1	69.9	73.5	81	66.1	69.9	73.5	81	
	Rated speed (r/min)	2300								
	Fuel	Diesel								
Tyre	Front Wheel	6.5-20				12.4-24				
	Rear Wheel	14.9-30 (16.9-34)				16.9-34				
Clutch		Dual-stage clutch								
Steering		Power steering								
Transmission Type		16F+8R								
Suspension Type		Three-point linkage Category II								
Lifting capacity(at point of 610mm) KN		22(Common lifter)/32.25(Higher pressure lifter)								
Lifting capacity(origin)KN		37(Common lifter)/54.6(Higher pressure lifter)								
PTO	Type and Rev	Semi-independent Type 540/1000								
	Spline Size	F35 Rectangle Spline with 6 teeth								

Structure and specification are subject to change without notice.

## 90-100HP TRACTOR

**Models:**

- Luzhong-900 tractor, 90HP 2WD, with 4-cylinder diesel engine
- Luzhong-950 tractor, 95HP 2WD, with 4-cylinder diesel engine
- Luzhong-1000 tractor, 100HP 2WD, with 4-cylinder diesel engine
- Luzhong-904 tractor, 90HP 4WD, with 4-cylinder diesel engine
- Luzhong-954 tractor, 95HP 4WD, with 4-cylinder diesel engine
- Luzhong-1004 tractor, 100HP 4WD, with 4-cylinder diesel engine

